

# General Aviation Modifications, Inc.

2800 Airport Rd. Hangar A  
Ada, OK 74820  
(580) 436-4833  
Fax (580) 436-6622

## MANUFACTURER RELEASE CERTIFICATE

KIT NO. GT16B

Product Name: **turboGAMIjectors**®  
Fuel Injection Nozzles

STC No. : **SE09289SC**  
FAA-PMA

P/N:GA262 Qty. 1 Installation Location Cylinder: 1 Replaces TCM P/N 632748-16B  
P/N:GA262 Qty. 1 Installation Location Cylinder: 2 Replaces TCM P/N 632748-16B  
P/N:GM246 Qty. 1 Installation Location Cylinder: 3 Replaces TCM P/N 632748-16B  
P/N:GM246 Qty. 1 Installation Location Cylinder: 4 Replaces TCM P/N 632748-16B  
P/N:GF235 Qty. 1 Installation Location Cylinder: 5 Replaces TCM P/N 632748-16B  
P/N:GF235 Qty. 1 Installation Location Cylinder: 6 Replaces TCM P/N 632748-16B

Applicable to:  
Engine Manufacturer :Teledyne Continental Motors

Engine Model(s): IO550D

**turboGAMIjectors**® Kit No. GT16B S/N 9673

THE AERONAUTICAL PRODUCT DESCRIBED HEREON CONFORMS TO APPROVED  
TYPE DESIGN AND IS IN A CONDITION FOR SAFE OPERATION



myh  
GAMI AUTHORIZED INSPECTOR

Date: 2-7-02

Date: February 6, 1997

***turboGAMljector*<sup>®</sup> Installation Procedure**  
**for TCM TSIO-520 and Turbonormalized IO-520 and IO-550 Engines**  
STC No. SE09289SC

1. Remove existing TCM fuel injector nozzles by disconnecting fuel and air lines at the top with an appropriate wrench. Remove the air lines surrounding each nozzle. Remove the nozzles with a ½ inch deep socket.
2. Determine which specific nozzle is installed in the engine as the factory standard nozzle. Then refer to Chart "T" for the GAMI Kit to be installed. Verify that the kit to be used matches the appropriate kit number corresponding to the factory standard nozzle size for the engine to be modified. Verify that the injectors enclosed in the kit are correctly identified and correspond to the injector numbers on the line identified by the kit number in Chart "T". Check to see that the "O" rings are properly installed in the respective grooves in the nozzles.
3. Using a ½ inch deep socket, install the *turboGAMljector*<sup>®</sup> nozzles in the appropriate cylinders as described above. It is recommended that an appropriate "anti-seize" compound be applied to the threads before installing the injectors.
4. Tighten nozzles to a torque value of 55-65 lb-in.
5. Reconnect and tighten the fuel and air lines at the top of the *turboGAMljector*<sup>®</sup> nozzles.
6. Check installation for crimped lines, loose fittings, etc.
7. Leak check the *turboGAMljector*<sup>®</sup> nozzles and associated fuel lines by use of the electric fuel pump, prior to starting the engine. Perform a ground engine run-up and recheck for fuel leaks before flight.
8. Clean a flat 1.5" X 2" area on each cylinder rocker arm cover with acetone or isopropyl alcohol. Apply the correct *turboGAMljector*<sup>®</sup> label to the cleaned area with high temperature RTV silicone, such as Permatex "Ultra Copper" P/N101B or equivalent. Allow to cure, thoroughly, prior to operation of the engine.
9. Check to insure that the *turboGAMljectors*<sup>®</sup> and placards have been installed on the proper cylinder and that the *turboGAMljector*<sup>®</sup> part number in each cylinder corresponds with the part number called out on the placard affixed to its respective cylinder head rocker arm cover.

